

MATERIAL SAFETY DATA SHEET

HLT FOMBLIN OIL Y 25/ 6

SECTION I – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: FOMBLIN Y-LVAC 25/6

CHEMICAL NAME: PROPENE, 1,1,2,3,3,3-HEXAFLUORO, OXIDIZED, POLYMERIZED

CHEMICAL FAMILY: FLUOROCARBONS, PERFLUORINATED POLYMERIZED

SYNONYMS: NONE

EMERGENCY TELEPHONE: 800-424-9300

CHEMTREC, 24 HOURS: 856-853-8119

EMERGENCY OVERVIEW: Clear, colorless liquid. Thermal decomposition will generate hydrogen fluoride (HF), which is corrosive.

SECTION II – COMPOSITIONAL INFORMATION

NAME:	CAS#	APPROXIMATE WEIGHT (%WT.)
PROPENE, 1,1,2,3,3,3-HEXA-FLUORO, OXIDIZED POLYMERIZED	69991-67-9	100

SECTION III – POTENTIAL HEALTH EFFECTS

EYE CONTACT: Eye contact may cause slight irritation.

SKIN CONTACT: Skin contact may cause slight irritation.

INHALATION: Inhalation of vapors or mist may cause respiratory tract irritation.

INGESTION: Not an expected exposure route. Ingestion may cause nausea and vomiting.

SECTION IV – FIRST AID MEASURES

EYE CONTACT: Flush eyes for 15 minutes with copious amounts of water, retracting eyelids often. Seek medical attention if irritation persists.

SKIN CONTACT: Wash skin thoroughly with mild soap and water. Flush with lukewarm water for 15 minutes.

INGESTION: If symptoms of irritation, discomfort or overcome by exposure, remove affected person to fresh air. Give oxygen or artificial respiration as needed.

INHALATION: If conscious, drink three to four 8 ounce glasses of water or milk. Call a physician. If unconscious, immediately take affected person to a hospital. Do not give anything by mouth to an unconscious person.

SECTION V – FIRE FIGHTING MEASURES

Flash Point:	Not Applicable
Lower Explosive Limit:	Not Applicable
Upper Explosive Limit:	Not Applicable
Autoignition Temperature:	Not Applicable
Extinguishing Media:	Water (spray or fog), foam, dry chemical or carbon dioxide (CO2)

Unusual Fire Hazards:

Fluoropolymers will degrade upon prolonged heating or in a fire, liberating carbonyl fluoride and hydrogen fluoride (HF). This gas is toxic if inhaled or it comes into contact with moist skin. HF has an ACGIH TLV ceiling limit of 3 ppm (2.6 mg/m³) and an OSHA PEL TWA of 3 ppm. Carbonyl fluoride has an ACGIH TLV TWA and OSHA PEL TWA of 2 ppm (5 mg/m³).

Fire Fighting Procedures:

Use self-contained breathing apparatus (SCBA) and skin protection for acid gas exposure. Do not enter fire area without proper protection. Fight fire from a safe distance. If possible, air monitoring should be performed.

SECTION VI – ACCIDENTAL RELEASE MEASURES

Releases:

In case of a release or spill, absorb material onto vermiculite or similar inert absorbent. Use Perfluorosolv0 PFS1 Solvent to clean any residual material. Place spilled material into covered container for disposal. Dispose of according to applicable local, state and federal regulations. Extinguish all ignition sources and evacuate the area. Exercise caution; spill area may be slippery.

SECTION VII – HANDLING AND STORAGE

Handling and Storage:

Wash hands after use and before handling food or applying cosmetics. Do not use tobacco products in the immediate area. Keep containers closed. Keep away from heat, sparks and flames. Do not store near combustible materials.

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

ACGIH Threshold Limit Value (8Hr. time weighted average)

None established

OSHA Permissible Exposure Limit Value (8Hr. time weighted average)

None established

Engineering Controls:**Ventilation Requirements:**

Local Exhaust: Vent vapors or mists generated by processing away from operating personnel. Local exhaust ventilation at a rate of 50 feet per minute.

Personal Protective Equipment:**Respiratory Protection:**

No occupational exposure standards have been developed for this material. In situations where exposure to vapors or mists is likely, NIOSH/MSHA approved respirators are recommended. Respirator use limitations made by NIOSH/MSHA or the manufacturer must be observed. Respiratory protection programs must be in accordance with 29 CFR 1910.134.

Eye Protection:

Eye / Face Protection: ANSI Z87.1 approved safety glasses with side shields or equivalent.

Skin Protection:

Rubber or latex gloves recommended but not necessary.

SECTION IX – PHYSICAL AND CHEMICAL PROPERTIES
--

Appearance:	Clear liquid
Color:	Colorless
Odor:	Odorless
Vapor Pressure:	Not available
Vapor Density (Air=1):	Not available
Boiling Point:	Not available
Melting Point:	Not available
Specific Gravity:	1.7 – 1.9
Solubility in Water:	Insoluble
Molecular Formula:	CF ₃ -[(O-CF ₂ -CF ₃ -CF ₂) _n (O-CF ₂) _m]-O-CF ₃
Molecular Weight:	Not available
% Volatile by Volume:	0

SECTION X – STABILITY AND REACTIVITY

STABILITY:	This material is stable.
REACTIVITY:	This material is not reactive.
CONDITIONS TO AVOID:	Heat, sparks, flames, and other ignition sources; avoid heating above 290°C / 554°F.
MATERIALS TO AVOID:	Strong or non-aqueous alkali or Lewis acids above 100°C / 212°F.
HAZARDOUS DECOMPOSITION PRODUCTS:	Thermal decomposition of this product will generate hydrogen fluoride (HF), which is corrosive, causing burns on contact with skin and other tissue.
INCOMPATIBILITY (MATERIALS TO AVOID):	Alkali metals and halogenated compounds.

SECTION XI – TOXICOLOGICAL INFORMATION

Rat Oral LD50:	Greater than 25.65 g/kg
Rat intraperitoneal LD50:	Greater than 25 g/kg
Rat dermal LD50:	Greater than 2 g/kg
Rabbit skin irritation:	Not irritating
Rabbit eye irritation:	Not irritating
Guinea pig sensitization:	Not a sensitizer

SECTION XII – ECOLOGICAL INFORMATION

No Eco toxicological information is available for this material.

SECTION XIII – DISPOSAL CONSIDERATIONS

Waste Disposal: Material, as supplied, is not a hazardous waste. Landfill according to current federal, state and local regulations, or incinerate in a high-temperature incinerator designed to burn fluorine-containing materials. Processing, use or contamination may make this information inaccurate or incomplete.

SECTION XIV – TRANSPORT INFORMATION

Shipping Class: Not regulated by DOT

SECTION XV – REGULATORY INFORMATION

All components of this product are listed on the Toxic Substances Control Act (TSCA) Section 8 (b) Chemical Inventory and the Canadian Environmental Protection Act (CEPA) provisional domestic substances list (DSL). This product is not a "hazardous substance" as defined by OSHA Hazard Communication Standard (29 CFR 1910.1200). This product is not a "controlled product" as defined by the Canadian Workplace Hazardous Materials Information System (WHMIS).

SARA Section 302 Extremely Hazardous Substances: Not listed

SARA 311/312:

Acute: No

Chronic: No

Fire: No

Reactivity: No

Sudden Release of Pressure: No

SARA Section 313 Toxic Chemicals: Not listed

SECTION XVI – ADDITIONAL INFORMATION**NFPA Ratings (Scale of 0 – 4):**

Health = 1

Fire = 0

Reactivity = 0

Helium Leak Testing, Inc. (HLT) Disclaimer: The above information is accurate to the best of our knowledge. However, HLT makes no warranty, either expressed or implied, with respect to the completeness or continuing accuracy of the information contained herein and disclaims all liability for reliance thereon.